

FSC VELLUM LASER PXL KB60

KSR7XEG15M

Edition: 1

Date of approval: 30/08/2017

Belongs to the collections

- Adhoc Rolls

Technical datasheet
Front Label

Reference	FSC VELLUM LASER
General characteristics	Woodfree white machine smoothed paper, with a high degree of whiteness FSC certified [FSC Mix ICILA-COC-000382]
Grammage (gr/m ²) ISO 536	70
Thickness (µm) ISO 534	75
Brightness (%) ISO 2470	113
Opacity (%) ISO 2471	85
Whitiness ISO 11475	166


Adhesive

Reference	PXL
General characteristics	Modified acrylic adhesive in water emulsion for A4 labels. Adhesive especially design for production of A4 labels, high initial tack, excellent adhesion also in low temperatures and apolar surfaces. This adhesive has been approved by FDA for indirect food contact and correspond to UNI-EN 71/3 Toys Security norms.
Tack (N) glass FTM-9	>8
Cohesion (h) 1 Kg FTM-8	>2
Labelling temperature (°C)	+5
Usage temperature (°C)	-20/+80

Support

Reference	KB60
General characteristics	White paper coated and siliconised on one side. There may be slight variations in tone. Backing paper for the continuous feed automatic printing application involving a low caliper sell adhesive paper. Not suitable for photocells dispensing systems.
Grammage (gr/m ²) ISO 536	52
Thickness (µm) ISO 534	54
Tensile strength MD/CD (KN/m) ISO 1924	MD>4,3 / CD>1,6

The technical specifications given are general in nature and based on our knowledge, for which reason the suitability of our products for the end use to which they are put cannot be guaranteed. It is the purchaser's responsibility to assess, test and ensure the suitability of each product for their end use through their own prior approval process; Arconvert S.p.A. cannot therefore be held responsible for unsuitable end use of its products. These technical product specifications supersede all previous editions. All information is subject to change without prior notice.

Schemes

Uses and applications

General all-purpose paper. Excellent printability with all conventional printing systems. Surface finishing ensures excellent results when using laser, needle or ink-jet printers.

Shelf life

2 years, under storage conditions as defined by FINAT section 2.5 (20-25°C, 40-50% RH).

ARCONVERT S.p.A.
 Codice Fiscale: 01077408882
 Partita I.V.A.: 01182310223
 Via L. Infante, 12 - 38062 ARCO
Stefano Zan